

## DESIGN ENVELOPE 4280 END SUCTION | 0410S007.5 | SUBMITTAL

File No: 100.3562  
Date: APRIL 18, 2016  
Supersedes: NEW  
Date: NEW

Job: \_\_\_\_\_ Representative: \_\_\_\_\_

Order No: \_\_\_\_\_ Date: \_\_\_\_\_

Engineer: \_\_\_\_\_ Submitted by: \_\_\_\_\_ Date: \_\_\_\_\_

Contractor: \_\_\_\_\_ Approved by: \_\_\_\_\_ Date: \_\_\_\_\_

### PUMP DESIGN DATA

No. of pumps: \_\_\_\_\_ Tag: \_\_\_\_\_  
Capacity: \_\_\_\_\_ USgpm (L/s) Head: \_\_\_\_\_ ft (m)  
Liquid: \_\_\_\_\_ Viscosity: \_\_\_\_\_  
Temperature: \_\_\_\_\_ °F (°C) Specific gravity: \_\_\_\_\_  
Suction: 5" (125mm) Tapped holes  
Discharge: 4" (100mm) Flanged  
OSHDP Seismic Certification **OSP-0422-10**  
UL STD 778 & CSA STD C22.2 NO.108 certified

### MOTOR DESIGN DATA

HP: 7.5 RPM: 1200 Frame size: 254JM  
Enclosure: TEFC Volts: \_\_\_\_\_ Hertz: 60 Hz  
Phase: 3 Efficiency: NEMA premium 12.12

### MAXIMUM PUMP OPERATING CONDITIONS

#### ANSI 125

175 psig at 150°F (12 bars at 65°C)  
140 psig at 250°F (10 bars at 121°C)

#### ANSI 250

300 psig at 150°F (20 bars at 65°C)  
250 psig at 250°F (17 bars at 121°C)

- Tolerance of ±0.125" (±3 mm) should be used
- For exact installation, data please write factory for certified dimensions

### MECHANICAL SEAL DATA

Seal type: 2A Stationary seat: Silicone carbide  
Secondary seal: EPDM Rotating hardware: Stainless steel  
Spring: Stainless steel

### CONTROLS DATA


Sensorless control: Standard  
Minimum system pressure to be maintained: \_\_\_\_\_ ft (m)\*  
Protocol (standard):  Modbus RTU  BACnet™ MS/TP  
 Johnson® N2  Siemens® FLN  
Protocol (optional):  LonWorks®  
Enclosure:  Indoor - UL TYPE 12  
Fused disconnect switch:   
EMI/RFI control: Integrated filter designed to meet EN61800-3  
Harmonic suppression: Dual DC-link reactors (equivalent: 5% AC line reactor) supporting IEEE 519-1992 requirements\*\*  
Cooling: Fan-cooled through back channel  
Ambient temperature: -10°C to +45°C up to 1000 meters above sea level (-14°F to +113°F, 3300 ft)  
Analog I/O: Two current or voltage inputs, one current output  
Digital I/O: Six programmable inputs (two can be configured as outputs)  
Pulse inputs: Two programmable  
Relay outputs: Two programmable  
Communication port: 1-RS485, 1-USB

\*If minimum maintained system pressure is not known: Default to 40% of design head

\*\*The Ivs 102 drive is a low harmonic drive via built-in DC line reactors. This does not guaranty performance to any system wide harmonic specification or the costs to meet a system wide specification. If supplied with the system electrical details, Armstrong will run a computer simulation of the system wide harmonics. If system harmonic levels are exceeded Armstrong can also recommend additional harmonic mitigation and the costs for such mitigation.

FLUID TYPE	ALL GLYCOLS > 30% WT CONC		ALL OTHER NON-POTABLE FLUIDS		POTABLE (DRINKING) WATER	
	up to 200°F / 93°C	over 200°F / 93°C	up to 200°F / 93°C	over 200°F / 93°C	up to 200°F / 93°C	over 200°F / 93°C
Temperature	up to 200°F / 93°C	over 200°F / 93°C	up to 200°F / 93°C	over 200°F / 93°C	up to 200°F / 93°C	over 200°F / 93°C
Rotating face	Silicone carbide		Resin bonded carbon	Antimony loaded carbon	Resin bonded carbon	
Seat elastomer	EPDM (L-cup)	EPDM (O-ring)	EPDM (L-cup)	EPDM (O-ring)	EPDM (L-cup)	EPDM (O-ring)
Material code	SCSc L EPSS 2A	SCSc O EPSS 2A	C-SC L EPSS 2A	ACSc O EPSS 2A	C-SC L EPSS 2A	C-SC O EPSS 2A

**EXTENDED SPEED**



Performance curves are for reference only.  
Confirm current performance data with Armstrong ACE Online selection software.

**DIMENSION DATA**

**INDOOR**  
(UL TYPE 12/ODP)

- Frame size: 254JM
- Size: 5×4×10
- HP: 7.5
- RPM: 1200
- A: 12.36 (314)
- B: 10.35 (263)
- C MAX: 28.23 (717)
- D1: 10.00 (254)
- D2: 6.25 (159)
- 2E: 10.00 (254)
- F: 8.25 (210)
- H: 0.59 (15)
- HD: 9.41 (239)
- HI: 23.57 (599)
- HV: 15.42 (392)
- N: 9.00 (229)
- NaN1: 9.75 (248)
- X: 12.50 (318)
- Y: 4.00 (102)
- Casing foot hole: 0.63 (16)
- Weight: 592 (268.5)

Dimensions - inch (mm)  
Weight - lbs (kg)

**INDOOR**

- TORONTO  
+1 416 755 2291
- BUFFALO  
+1 716 693 8813
- BIRMINGHAM  
+44 (0) 8444 145 145
- MANCHESTER  
+44 (0) 8444 145 145
- BANGALORE  
+91 (0) 80 4906 3555
- SHANGHAI  
+86 21 3756 6696
- SÃO PAULO  
+55 11 4781 5500

