



EXCHANGER SIZE	DIMENSIONS											
	A		B		C		D		N1		N2	
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm
WSX-203-2E4	78 3/4	2000	36 7/8	937	21	533	41	1041	12	305	4	102
WSX-204-2E4	90 3/4	2305	48 7/8	1241	33	838	53	1346	12	305	4	102
WSX-205-2E4	102 3/4	2610	60 7/8	1546	45	1143	65	1651	12	305	4	102
WSX-206-2E4	114 3/4	2915	72 7/8	1851	57	1448	77	1956	12	305	4	102
WSX-207-2E4	126 3/4	3219	84 7/8	2156	69	1753	89	2261	12	305	4	102
WSX-208-2E4	138 3/4	3524	96 7/8	2461	81	2057	101	2565	12	305	4	102
WSX-209-2E4	150 3/4	3829	108 7/8	2765	93	2362	113	2870	12	305	4	102
WSX-2010-2E4	162 3/4	4134	120 7/8	3070	105	2667	125	3175	12	305	4	102
WSX-2011-2E4	174 3/4	4439	132 7/8	3375	117	2972	137	3480	12	305	4	102
WSX-2012-2E4	186 3/4	4743	144 7/8	3680	129	3277	149	3785	12	305	4	102
WSX-2013-2E4	198 3/4	5048	156 7/8	3985	141	3581	161	4089	12	305	4	102
WSX-2014-2E4	210 3/4	5353	168 7/8	4289	153	3886	173	4394	12	305	4	102
WSX-2015-2E4	222 3/4	5658	180 7/8	4594	165	4191	185	4699	12	305	4	102

NOZZLE SCHEDULE				
SERVICE	MARK	SHELL SIDE	MARK	TUBE SIDE
INLET	N1	AS PER TABLE	N5	8 (203) FLG
OUTLET	N2	AS PER TABLE	N6	8 (203) FLG
DRAIN	N3	3/4 (19) NPT		
VENT	N4	3/4 (19) NPT		

NOTES: 1. SUPPORTS SUPPLIED ONLY IF SPECIFIED ON ORDER.
 2. NOZZLE SIZES SHOWN ARE RECOMMENDED FOR MAXIMUM EXCHANGER LIFE.
 3. FABRICATED TO ASME CODE SECTION VIII DIVISION 1 AND LATEST ADDENDA.
 4. DRAWING IS NOT TO SCALE.
 5. ALL DIM'S ±1/8 (3) UNLESS OTHERWISE SHOWN.

DESIGN CONDITIONS				
	SHELL		TUBES	
DESIGN PRESSURE	150 PSIG	1034 KP _a	150 PSIG	1034 KP _a
DESIGN TEMPERATURE	375 °F	191 °C	375 °F	191 °C
MIN. DESIGN METAL TEMP.	40 °F	4.4 °C	40 °F	4.4 °C
HYDRO. TEST PRESSURE	225 PSIG	1551 KP _a	225 PSIG	1551 KP _a
CONTENTS	STEAM		WATER	

CUSTOMER:
 LOCATION:
 ENGINEER:
 ORDER No.:
 PROJECT/JOB:
 LOCATION:
 TAG: (QUOTE #)

TITLE	A R M S T R O N G				NUMBER	REV.
G.A. 150 LB. WSX SERIES HEAT EXCHANGERS	TORONTO - CANADA	MONTREAL - CANADA	BUFFALO - N. Y.	COLCHESTER - U.K.	WSX-20-2P-E4	
DATE: 12/01/94 BY: D.C.R.	TEL: (416) 755-2291	TEL: (514) 421-2424	TEL: (716) 693-8813	TEL: (44) 120-657-9491		