



DIMENSIONS SHOWN AS: inches (mm)

EXCHANGER SIZE *-BAFFLE SPACING	DIMENSIONS											
	A		B		C		D		N1		N2	
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm
WX-164-2*-2	65 5/8	1667	32 1/4	819	17 3/4	451	52	1321	8	203	8	203
WX-165-2*-2	77 5/8	1972	44 1/4	1124	29 3/4	756	64	1626	8	203	8	203
WX-166-2*-2	89 5/8	2276	56 1/4	1429	41 3/4	1060	76	1930	8	203	8	203
WX-167-2*-2	101 5/8	2581	68 1/4	1734	53 3/4	1365	88	2235	8	203	8	203
WX-168-2*-2	113 5/8	2886	80 1/4	2038	65 3/4	1670	100	2540	8	203	8	203
WX-169-2*-2	125 5/8	3191	92 1/4	2343	77 3/4	1975	112	2845	8	203	8	203
WX-1610-2*-2	137 5/8	3496	104 1/4	2648	89 3/4	2280	124	3150	8	203	8	203
WX-1611-2*-2	149 5/8	3800	116 1/4	2953	101 3/4	2584	136	3454	8	203	8	203
WX-1612-2*-2	161 5/8	4105	128 1/4	3258	113 3/4	2889	148	3759	8	203	8	203
WX-1613-2*-2	173 5/8	4410	140 1/4	3562	125 3/4	3194	160	4064	8	203	8	203
WX-1614-2*-2	185 5/8	4715	152 1/4	3867	137 3/4	3499	172	4369	8	203	8	203
WX-1615-2*-2	197 5/8	5020	164 1/4	4172	149 3/4	3804	184	4674	8	203	8	203

NOZZLE SCHEDULE				
SERVICE	MARK	SHELL SIDE	MARK	TUBE SIDE
INLET	N1	AS PER TABLE	N5	6 (152) FLG
OUTLET	N2	AS PER TABLE	N6	6 (152) FLG
DRAIN	N3	1/2 (13) NPT		
VENT	N4	3/4 (19) NPT		

- NOTES: 1. SUPPORTS SUPPLIED ONLY IF SPECIFIED ON ORDER.
 2. NOZZLE SIZES SHOWN ARE RECOMMENDED FOR MAXIMUM EXCHANGER LIFE.
 3. FABRICATED TO ASME CODE SECTION VIII DIVISION 1 AND LATEST ADDENDA.
 4. DRAWING IS NOT TO SCALE.
 5. ALL DIMN'S ±1/8 (3) UNLESS OTHERWISE SHOWN.

DESIGN CONDITIONS				
	SHELL		TUBES	
DESIGN PRESSURE	150 PSIG	1034 KPa	150 PSIG	1034 KPa
DESIGN TEMPERATURE	375 °F	191 °C	375 °F	191 °C
MIN. DESIGN METAL TEMP.	40 °F	4.4 °C	40 °F	4.4 °C
HYDRO. TEST PRESSURE	225 PSIG	1551 KPa	300 PSIG	2068 KPa
CONTENTS	WATER		WATER	

CUSTOMER:
 LOCATION:
 ENGINEER:
 ORDER No.:
 PROJECT/JOB:
 LOCATION:
 TAG: (QUOTE #)

TITLE	G.A. 150 LB. WX SERIES HEAT EXCHANGERS	A R M S T R O N G				NUMBER	WX-16-2P-2(8)	REV.			
DATE:	12 / 01 / 94	BY:	D.C.R.	TORONTO - CANADA	MONTREAL - CANADA	BUFFALO - N. Y.	COLCHESTER - U.K.	TEL: (416) 755-2291	TEL: (514) 421-2424	TEL: (716) 693-8813	TEL: (44) 120-657-9491